

## SOIL INFORMATION

## TRIAL INFORMATION

TEXTURE: SIL  
PH: 6.6  
%OM: 4.7  
PREV.CROP: ZEAMD - CORN, DENT  
%RESIDUE: 0  
PLOT WIDTH: 7.5 X 30 FEET

DESIGN: RCB  
REPS: 3

| APPL. NUMBER       | 01        | 02        | 03        | UNIT |
|--------------------|-----------|-----------|-----------|------|
| TIMINGS            | 09        | 12        | 13        |      |
| TYPE               | LIQMIX    | LIQMIX    | LIQMIX    |      |
| APPLICATION DATE   | 05/12/04  | 06/17/04  | 06/23/04  | AME  |
| AIR TEMPERATURE    | 84        | 83        | 80        | F    |
| % REL.HUMIDITY     | 55        | 70        | 45        |      |
| WIND DIRECTION     | SOUTH     | WEST      | SOUTHWEST |      |
| WIND SPEED         | 12.0      | 2.0       | 5.0       | M/H  |
| CLOUD COVER        | PARTCLDY  | PARTCLDY  | CLEAR     |      |
| DEW                | NO        | NO        | NO        |      |
| SOIL MOISTURE      | DRY/MOIST | MOIST/MOI | DRY/MOIST |      |
| SOIL CONDITION     | ---       | ---       | ---       |      |
| METHOD             | SPRAY     | SPRAY     | SPRAY     |      |
| EQUIPMENT          | SPRBAC    | SPRBAC    | SPRBAC    |      |
| PROPELLANT         | COMCO2    | COMCO2    | COMCO2    |      |
| PLACEMENT          | BRFOSO    | BRFOSO    | BRFOSO    |      |
| NOZZLE             | FLATFAN   | FLATFAN   | FLATFAN   |      |
| NOZZLE NUMBER      | 5         | 5         | 5         |      |
| NOZZLE SPACING     | 18.000    | 18.000    | 18.000    | IN   |
| SWATH WIDTH        | 7.5       | 7.5       | 7.5       | FT   |
| SPRAY VOLUME       | 20.00     | 20.00     | 20.00     |      |
| VOLUME UNIT        | GPA       | GPA       | GPA       |      |
| PRESSURE           | 30.00     | 30.00     | 30.00     | PSI  |
| DILUENT            | WATER     | WATER     | WATER     |      |
| INC. DATE          |           |           |           | AME  |
| INC. START         |           |           |           | 24H  |
| INC. END           |           |           |           | 24H  |
| INC. DEPTH         |           |           |           | IN   |
| INC. EQUIPMENT     | ---       | ---       | ---       |      |
| DEN/ STG/ MINMAXSZ |           |           |           |      |
| *** CROP ***       |           |           |           |      |
| SOYBEAN            |           | ---/14    | ---/15    |      |
| PIONEER 93B67      |           | 8.00/10.0 | 12.0/12.0 | IN   |
| 05/12/2004         |           |           |           |      |
| *** PEST ***       |           |           |           |      |
| VELVETLEAF         |           | ---/15    | ---/17    |      |
|                    |           | 3.00/6.00 | 4.00/8.00 | IN   |
| LAMBSQUARTERS, C   |           | ---/19    | ---/19    |      |
|                    |           | 3.00/6.00 | 4.00/8.00 | IN   |
| MORNINGGLORY, TA   |           | ---/15    | ---/18    |      |
|                    |           | 2.00/4.00 | 3.00/5.00 | IN   |
| SMARTWEED, PENNS   |           | ---/19    | ---/19    |      |
|                    |           | 3.00/6.00 | 4.00/8.00 | IN   |
| FOXTAIL, GIANT     |           | ---/16    | ---/15    |      |
|                    |           | 4.00/8.00 | 6.00/10.0 | IN   |
| CORN, VOLUNTEER,   |           | ---/16    | ---/19    |      |
|                    |           | 18.0/24.0 | 20.0/28.0 | IN   |

## \* TIMING CODES

09 = ----- / PREEMERGENCE  
12 = ----- / POST  
13 = ----- / LPOST

## \* STAGE CODE

14 = 4TH LEAF (2ND TRIFOLIATE LEAF) UNFOLDED, 3 NODES  
15 = 5TH TRUE LEAVES/LEAF PAIRS/WHORLS UNFOLDED  
16 = 6 LEAVES UNFOLDED  
17 = 7TH TRUE LEAVES/LEAF PAIRS/WHORLS UNFOLDED  
18 = 8TH TRUE LEAVES/LEAF PAIRS/WHORLS UNFOLDED  
19 = >8 TRUE LEAVES/LEAF PAIRS/WHORLS UNFOLDED

**TITLE:** VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200  
**CREATED:** 04/22/2004 **REVISED:** 11/16/2004 **COMPLETED:** N  
**PROJECT TYPE:** HERBICIDE  
**LOCATION:** Urbana **RESEARCHED BY:** UNIV. OF ILL  
**DESIGN:** RANDOMIZED COMPLETE BLOCK DESIGN  
**PLOT SIZE:** 7.50 FT **WIDE X** 30.00 FT **LONG**

**REPS:** 03

| TRT TREATMENT     | DOSAGE       | GLXMA    | SETFA    | ZEAMX    | CHEAL    | POLPY    | ABUTH    |
|-------------------|--------------|----------|----------|----------|----------|----------|----------|
| NUM COMPONENT     | RATE UNIT TM | CON %    | CON %    | CON %    | CON %    | CON %    | CON %    |
|                   |              | 06/16/04 | 06/16/04 | 06/16/04 | 06/16/04 | 06/16/04 | 06/16/04 |
| 1A»CANOPY XL 56.3 | 0.24 LAA 0   | 0        | 77       | 47       | 99       | 99       | 99       |
| B»AUTHORITY       | 0.20 LAA 9   |          |          |          |          |          |          |
| C CLASSIC 25WG    | 0.04 LAA 9   |          |          |          |          |          |          |
| 2A»SPARTAN 4L     | 0.30 LAA 9   | 5        | 95       | 20       | 99       | 99       | 99       |
| B COMMAND 3ME     | 0.60 LAA 9   |          |          |          |          |          |          |
| 3A PURSUIT +      | 0.91 LAA 9   | 0        | 92       | 53       | 99       | 99       | 99       |
| 4A»EXTREME 2.17L  | 0.81 LAA 12  |          |          |          |          |          |          |
| B»ACTIVATOR 90    | 0.25 PMV 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 5.00 PMV 12  |          |          |          |          |          |          |
| 5A PURSUIT DG (70 | 0.063 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 6A»RAPTOR 1AS     | 0.031 LAA 12 |          |          |          |          |          |          |
| B»MSO             | 1.00 PMV 12  |          |          |          |          |          |          |
| C 28% UAN         | 2.50 PMV 12  |          |          |          |          |          |          |
| 7A POAST + 1EC    | 0.188 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 8A ASSURE II (0.8 | 0.034 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 9A FUSION         | 0.125 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 10A»ARROW 2EC     | 0.063 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 11A»ARROW 2EC     | 0.031 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 12A SCEPTER 70DG  | 0.031 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 13A SCEPTER 70DG  | 0.063 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 14A SCEPTER 70DG  | 0.031 LAA 13 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 13  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 13  |          |          |          |          |          |          |
| 15A SCEPTER 70DG  | 0.063 LAA 13 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 13  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 13  |          |          |          |          |          |          |
| 16A SELECT (2EC)  | 0.063 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 17A»V-10137 1EC   | 0.063 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 18A SELECT (2EC)  | 0.047 LAA 12 |          |          |          |          |          |          |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |

## TITLE: VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200

| TRT                | TREATMENT        | DOSAGE |      | GLXMA | SETFA    | ZEAMX    | CHEAL    | POLPY    | ABUTH    |
|--------------------|------------------|--------|------|-------|----------|----------|----------|----------|----------|
| NUM                | COMPONENT        | RATE   | UNIT | TM    | CON %    | CON %    | CON %    | CON %    | CON %    |
|                    |                  |        |      |       | 06/16/04 | 06/16/04 | 06/16/04 | 06/16/04 | 06/16/04 |
| 19A»               | V-10137 1EC      | 0.047  | LAA  | 12    |          |          |          |          |          |
|                    | B»WEATHERMAX 4.5 | 0.75   | LAA  | 12    |          |          |          |          |          |
|                    | C»LIQUID AMS     | 2.50   | PMV  | 12    |          |          |          |          |          |
| 20A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
| 21A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
|                    | C»N-PAK AMS      | 2.50   | PMV  | 12    |          |          |          |          |          |
| 22A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
|                    | C»ALLIANCE       | 1.25   | PMV  | 12    |          |          |          |          |          |
| 23A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
|                    | C»DESTINY        | 1.00   | PMV  | 12    |          |          |          |          |          |
|                    | D»N-PAK AMS      | 2.50   | PMV  | 12    |          |          |          |          |          |
| 24A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
|                    | C»PREFERENCE     | 0.25   | PMV  | 12    |          |          |          |          |          |
|                    | D»N-PAK AMS      | 2.50   | PMV  | 12    |          |          |          |          |          |
| 25A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
|                    | C»SUPERB HC      | 0.50   | PMV  | 12    |          |          |          |          |          |
|                    | D»N-PAK AMS      | 2.50   | PMV  | 12    |          |          |          |          |          |
| 26A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
|                    | C»SUPERB HC      | 0.50   | PMV  | 12    |          |          |          |          |          |
|                    | D»ALLIANCE       | 1.25   | PMV  | 12    |          |          |          |          |          |
| 27A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B SELECT (2EC)   | 0.031  | LAA  | 12    |          |          |          |          |          |
|                    | C»AG 03002       | 1.00   | PMV  | 12    |          |          |          |          |          |
| 28A»               | WEATHERMAX 4.5   | 0.56   | LAA  | 12    |          |          |          |          |          |
|                    | B»AG 03002       | 1.50   | PMV  | 12    |          |          |          |          |          |
| LSD (0.05)         |                  |        |      |       | 6.54     | 13.81    | 29.26    | 0.00     | 0.00     |
| STANDARD DEVIATION |                  |        |      |       | 2.36     | 5.00     | 10.54    | 0.00     | 0.00     |

**TITLE:** VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200  
**CREATED:** 04/22/2004 **REVISED:** 11/16/2004 **COMPLETED:** N  
**PROJECT TYPE:** HERBICIDE  
**LOCATION:** Urbana **RESEARCHED BY:** UNIV. OF ILL  
**DESIGN:** RANDOMIZED COMPLETE BLOCK DESIGN  
**PLOT SIZE:** 7.50 FT **WIDE X** 30.00 FT **LONG**

REPS: 03

| TRT TREATMENT     | DOSAGE       | PHBPU    | GLXMA    | SETFA    | ZEAMX    | CHEAL    | POLPY    |
|-------------------|--------------|----------|----------|----------|----------|----------|----------|
| NUM COMPONENT     | RATE UNIT TM | CON %    | CON %    | CON %    | CON %    | CON %    | CON %    |
|                   |              | 06/16/04 | 06/30/04 | 06/30/04 | 06/30/04 | 06/30/04 | 06/30/04 |
| 1A»CANOPY XL 56.3 | 0.24 LAA 0   | 96       | 0        | 43       | 27       | 99       | 98       |
| B»AUTHORITY       | 0.20 LAA 9   |          |          |          |          |          |          |
| C CLASSIC 25WG    | 0.04 LAA 9   |          |          |          |          |          |          |
| 2A»SPARTAN 4L     | 0.30 LAA 9   | 97       | 0        | 94       | 0        | 99       | 91       |
| B COMMAND 3ME     | 0.60 LAA 9   |          |          |          |          |          |          |
| 3A PURSUIT +      | 0.91 LAA 9   | 82       | 0        | 96       | 43       | 99       | 99       |
| 4A»EXTREME 2.17L  | 0.81 LAA 12  |          | 0        | 99       | 80       | 99       | 99       |
| B»ACTIVATOR 90    | 0.25 PMV 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 5.00 PMV 12  |          |          |          |          |          |          |
| 5A PURSUIT DG (70 | 0.063 LAA 12 |          | 0        | 99       | 78       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 6A»RAPTOR 1AS     | 0.031 LAA 12 |          | 0        | 96       | 93       | 96       | 98       |
| B»MSO             | 1.00 PMV 12  |          |          |          |          |          |          |
| C 28% UAN         | 2.50 PMV 12  |          |          |          |          |          |          |
| 7A POAST + 1EC    | 0.188 LAA 12 |          | 0        | 99       | 91       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 8A ASSURE II (0.8 | 0.034 LAA 12 |          | 0        | 99       | 97       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 9A FUSION         | 0.125 LAA 12 |          | 0        | 99       | 96       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 10A»ARROW 2EC     | 0.063 LAA 12 |          | 0        | 99       | 92       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 11A»ARROW 2EC     | 0.031 LAA 12 |          | 0        | 99       | 88       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 12A SCEPTER 70DG  | 0.031 LAA 12 |          | 0        | 99       | 77       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 13A SCEPTER 70DG  | 0.063 LAA 12 |          | 0        | 99       | 84       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 14A SCEPTER 70DG  | 0.031 LAA 13 |          | 0        | 98       | 65       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 13  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 13  |          |          |          |          |          |          |
| 15A SCEPTER 70DG  | 0.063 LAA 13 |          | 0        | 96       | 84       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 13  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 13  |          |          |          |          |          |          |
| 16A SELECT (2EC)  | 0.063 LAA 12 |          | 0        | 99       | 96       | 99       | 98       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 17A»V-10137 1EC   | 0.063 LAA 12 |          | 0        | 99       | 96       | 98       | 98       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |
| 18A SELECT (2EC)  | 0.047 LAA 12 |          | 0        | 99       | 94       | 99       | 99       |
| B»WEATHERMAX 4.5  | 0.75 LAA 12  |          |          |          |          |          |          |
| C»LIQUID AMS      | 2.50 PMV 12  |          |          |          |          |          |          |

TITLE: VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200

| TRT                | TREATMENT        | DOSAGE | PHBPU  | GLXMA    | SETFA    | ZEAMX    | CHEAL    | POLPY    |
|--------------------|------------------|--------|--------|----------|----------|----------|----------|----------|
| NUM                | COMPONENT        | RATE   | CON %  | CON %    | CON %    | CON %    | CON %    | CON %    |
|                    |                  | UNIT   | TM     | 06/16/04 | 06/30/04 | 06/30/04 | 06/30/04 | 06/30/04 |
| 19A»               | V-10137 1EC      | 0.047  | LAA 12 |          | 0        | 99       | 93       | 99       |
|                    | B»WEATHERMAX 4.5 | 0.75   | LAA 12 |          |          |          |          |          |
|                    | C»LIQUID AMS     | 2.50   | PMV 12 |          |          |          |          |          |
| 20A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 84       | 99       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
| 21A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 88       | 99       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
|                    | C»N-PAK AMS      | 2.50   | PMV 12 |          |          |          |          |          |
| 22A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 89       | 99       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
|                    | C»ALLIANCE       | 1.25   | PMV 12 |          |          |          |          |          |
| 23A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 91       | 99       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
|                    | C»DESTINY        | 1.00   | PMV 12 |          |          |          |          |          |
|                    | D»N-PAK AMS      | 2.50   | PMV 12 |          |          |          |          |          |
| 24A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 93       | 99       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
|                    | C»PREFERENCE     | 0.25   | PMV 12 |          |          |          |          |          |
|                    | D»N-PAK AMS      | 2.50   | PMV 12 |          |          |          |          |          |
| 25A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 95       | 99       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
|                    | C»SUPERB HC      | 0.50   | PMV 12 |          |          |          |          |          |
|                    | D»N-PAK AMS      | 2.50   | PMV 12 |          |          |          |          |          |
| 26A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 97       | 99       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
|                    | C»SUPERB HC      | 0.50   | PMV 12 |          |          |          |          |          |
|                    | D»ALLIANCE       | 1.25   | PMV 12 |          |          |          |          |          |
| 27A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 94       | 96       |
|                    | B SELECT (2EC)   | 0.031  | LAA 12 |          |          |          |          |          |
|                    | C»AG 03002       | 1.00   | PMV 12 |          |          |          |          |          |
| 28A»               | WEATHERMAX 4.5   | 0.56   | LAA 12 |          | 0        | 99       | 0        | 97       |
|                    | B»AG 03002       | 1.50   | PMV 12 |          |          |          |          |          |
| LSD (0.05)         |                  |        |        | 14.63    | 0.00     | 4.89     | 5.29     | 1.63     |
| STANDARD DEVIATION |                  |        |        | 5.27     | 0.00     | 2.44     | 2.65     | 0.815    |
|                    |                  |        |        |          |          |          |          | 3.12     |
|                    |                  |        |        |          |          |          |          | 1.56     |

**TITLE:** VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200  
**CREATED:** 04/22/2004 **REVISED:** 11/16/2004 **COMPLETED:** N  
**PROJECT TYPE:** HERBICIDE  
**LOCATION:** Urbana **RESEARCHED BY:** UNIV. OF ILL  
**DESIGN:** RANDOMIZED COMPLETE BLOCK DESIGN  
**PLOT SIZE:** 7.50 FT **WIDE X** 30.00 FT **LONG** **REPS:** 03

| TRT TREATMENT<br>NUM COMPONENT | DOSAGE<br>RATE UNIT | TM     | ABUTH<br>CON %<br>06/30/04 | PHBPU<br>CON %<br>06/30/04 | GLXMA<br>CON %<br>07/16/04 | SETFA<br>CON %<br>07/16/04 | ZEAMX<br>CON %<br>07/16/04 | CHEAL<br>CON %<br>07/16/04 |
|--------------------------------|---------------------|--------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| 1A»CANOPY XL 56.3              | 0.24                | LAA 0  | 88                         | 85                         | 0                          | 33                         | 23                         | 99                         |
| B»AUTHORITY                    | 0.20                | LAA 9  |                            |                            |                            |                            |                            |                            |
| C CLASSIC 25WG                 | 0.04                | LAA 9  |                            |                            |                            |                            |                            |                            |
| 2A»SPARTAN 4L                  | 0.30                | LAA 9  | 99                         | 93                         | 0                          | 92                         | 0                          | 99                         |
| B COMMAND 3ME                  | 0.60                | LAA 9  |                            |                            |                            |                            |                            |                            |
| 3A PURSUIT +                   | 0.91                | LAA 9  | 99                         | 82                         | 0                          | 96                         | 27                         | 99                         |
| 4A»EXTREME 2.17L               | 0.81                | LAA 12 | 99                         | 94                         | 5                          | 99                         | 84                         | 99                         |
| B»ACTIVATOR 90                 | 0.25                | PMV 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 5.00                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 5A PURSUIT DG (70              | 0.063               | LAA 12 | 99                         | 94                         | 2                          | 99                         | 79                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 6A»RAPTOR 1AS                  | 0.031               | LAA 12 | 99                         | 86                         | 7                          | 97                         | 97                         | 93                         |
| B»MSO                          | 1.00                | PMV 12 |                            |                            |                            |                            |                            |                            |
| C 28% UAN                      | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 7A POAST + 1EC                 | 0.188               | LAA 12 | 99                         | 89                         | 0                          | 99                         | 98                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 8A ASSURE II (0.8              | 0.034               | LAA 12 | 99                         | 93                         | 0                          | 99                         | 99                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 9A FUSION                      | 0.125               | LAA 12 | 99                         | 93                         | 0                          | 99                         | 99                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 10A»ARROW 2EC                  | 0.063               | LAA 12 | 99                         | 93                         | 0                          | 99                         | 97                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 11A»ARROW 2EC                  | 0.031               | LAA 12 | 99                         | 93                         | 0                          | 99                         | 95                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 12A SCEPTER 70DG               | 0.031               | LAA 12 | 99                         | 92                         | 0                          | 99                         | 89                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 13A SCEPTER 70DG               | 0.063               | LAA 12 | 99                         | 92                         | 0                          | 99                         | 89                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 14A SCEPTER 70DG               | 0.031               | LAA 13 | 99                         | 78                         | 0                          | 99                         | 75                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 13 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 13 |                            |                            |                            |                            |                            |                            |
| 15A SCEPTER 70DG               | 0.063               | LAA 13 | 99                         | 77                         | 0                          | 99                         | 84                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 13 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 13 |                            |                            |                            |                            |                            |                            |
| 16A SELECT (2EC)               | 0.063               | LAA 12 | 99                         | 89                         | 0                          | 99                         | 98                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 17A»V-10137 1EC                | 0.063               | LAA 12 | 99                         | 88                         | 0                          | 99                         | 98                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |
| 18A SELECT (2EC)               | 0.047               | LAA 12 | 99                         | 91                         | 0                          | 99                         | 97                         | 99                         |
| B»WEATHERMAX 4.5               | 0.75                | LAA 12 |                            |                            |                            |                            |                            |                            |
| C»LIQUID AMS                   | 2.50                | PMV 12 |                            |                            |                            |                            |                            |                            |

TITLE: VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200

| TRT<br>NUM         | TREATMENT<br>COMPONENT | DOSAGE<br>RATE | UNIT | TM | ABUTH<br>CON %<br>06/30/04 | PHBPU<br>CON %<br>06/30/04 | GLXMA<br>CON %<br>07/16/04 | SETFA<br>CON %<br>07/16/04 | ZEAMX<br>CON %<br>07/16/04 | CHEAL<br>CON %<br>07/16/04 |
|--------------------|------------------------|----------------|------|----|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| 19A»V-10137        | 1EC                    | 0.047          | LAA  | 12 | 99                         | 84                         | 0                          | 99                         | 97                         | 99                         |
|                    | B»WEATHERMAX 4.5       | 0.75           | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»LIQUID AMS           | 2.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 20A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 74                         | 0                          | 99                         | 68                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
| 21A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 89                         | 0                          | 99                         | 91                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»N-PAK AMS            | 2.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 22A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 88                         | 0                          | 99                         | 92                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»ALLIANCE             | 1.25           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 23A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 89                         | 0                          | 99                         | 99                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»DESTINY              | 1.00           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
|                    | D»N-PAK AMS            | 2.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 24A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 91                         | 0                          | 99                         | 96                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»PREFERENCE           | 0.25           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
|                    | D»N-PAK AMS            | 2.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 25A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 94                         | 0                          | 99                         | 99                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»SUPERB HC            | 0.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
|                    | D»N-PAK AMS            | 2.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 26A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 95                         | 0                          | 99                         | 98                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»SUPERB HC            | 0.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
|                    | D»ALLIANCE             | 1.25           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 27A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 93                         | 0                          | 99                         | 97                         | 99                         |
|                    | B SELECT (2EC)         | 0.031          | LAA  | 12 |                            |                            |                            |                            |                            |                            |
|                    | C»AG 03002             | 1.00           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| 28A»WEATHERMAX     | 4.5                    | 0.56           | LAA  | 12 | 99                         | 87                         | 0                          | 99                         | 0                          | 99                         |
|                    | B»AG 03002             | 1.50           | PMV  | 12 |                            |                            |                            |                            |                            |                            |
| LSD (0.05)         |                        |                |      |    | 3.00                       | 7.35                       | 1.24                       | 2.29                       | 5.75                       | 1.08                       |
| STANDARD DEVIATION |                        |                |      |    | 1.52                       | 3.68                       | 0.618                      | 1.15                       | 2.88                       | 0.542                      |

**TITLE:** VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200  
**CREATED:** 04/22/2004 **REVISED:** 11/16/2004 **COMPLETED:** N  
**PROJECT TYPE:** HERBICIDE  
**LOCATION:** Urbana **RESEARCHED BY:** UNIV. OF ILL  
**DESIGN:** RANDOMIZED COMPLETE BLOCK DESIGN  
**PLOT SIZE:** 7.50 FT **WIDE X** 30.00 FT **LONG** **REPS:** 03

| TRT TREATMENT<br>NUM COMPONENT | DOSAGE<br>RATE | UNIT | TM | POLPY<br>CON %<br>07/16/04 | ABUTH<br>CON %<br>07/16/04 | PHBPU<br>CON %<br>07/16/04 |
|--------------------------------|----------------|------|----|----------------------------|----------------------------|----------------------------|
| 1A»CANOPY XL 56.3              | 0.24           | LAA  | 0  | 99                         | 99                         | 67                         |
| B»AUTHORITY                    | 0.20           | LAA  | 9  |                            |                            |                            |
| C CLASSIC 25WG                 | 0.04           | LAA  | 9  |                            |                            |                            |
| 2A»SPARTAN 4L                  | 0.30           | LAA  | 9  | 99                         | 99                         | 93                         |
| B COMMAND 3ME                  | 0.60           | LAA  | 9  |                            |                            |                            |
| 3A PURSUIT +                   | 0.91           | LAA  | 9  | 99                         | 92                         | 78                         |
| 4A»EXTREME 2.17L               | 0.81           | LAA  | 12 | 99                         | 99                         | 93                         |
| B»ACTIVATOR 90                 | 0.25           | PMV  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 5.00           | PMV  | 12 |                            |                            |                            |
| 5A PURSUIT DG (70              | 0.063          | LAA  | 12 | 99                         | 99                         | 93                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 6A»RAPTOR 1AS                  | 0.031          | LAA  | 12 | 95                         | 99                         | 84                         |
| B»MSO                          | 1.00           | PMV  | 12 |                            |                            |                            |
| C 28% UAN                      | 2.50           | PMV  | 12 |                            |                            |                            |
| 7A POAST + 1EC                 | 0.188          | LAA  | 12 | 99                         | 99                         | 92                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 8A ASSURE II (0.8              | 0.034          | LAA  | 12 | 99                         | 99                         | 92                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 9A FUSION                      | 0.125          | LAA  | 12 | 99                         | 99                         | 93                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 10A»ARROW 2EC                  | 0.063          | LAA  | 12 | 99                         | 99                         | 91                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 11A»ARROW 2EC                  | 0.031          | LAA  | 12 | 99                         | 99                         | 94                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 12A SCEPTER 70DG               | 0.031          | LAA  | 12 | 99                         | 99                         | 94                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 13A SCEPTER 70DG               | 0.063          | LAA  | 12 | 99                         | 99                         | 92                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 14A SCEPTER 70DG               | 0.031          | LAA  | 13 | 99                         | 99                         | 87                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 13 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 13 |                            |                            |                            |
| 15A SCEPTER 70DG               | 0.063          | LAA  | 13 | 99                         | 99                         | 84                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 13 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 13 |                            |                            |                            |
| 16A SELECT (2EC)               | 0.063          | LAA  | 12 | 99                         | 99                         | 90                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 17A»V-10137 1EC                | 0.063          | LAA  | 12 | 99                         | 99                         | 91                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 18A SELECT (2EC)               | 0.047          | LAA  | 12 | 99                         | 99                         | 91                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |

TITLE: VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200

| TRT TREATMENT<br>NUM COMPONENT | DOSAGE<br>RATE | UNIT | TM | POLPY<br>CON %<br>07/16/04 | ABUTH<br>CON %<br>07/16/04 | PHBPU<br>CON %<br>07/16/04 |
|--------------------------------|----------------|------|----|----------------------------|----------------------------|----------------------------|
| 19A»V-10137 1EC                | 0.047          | LAA  | 12 | 99                         | 99                         | 88                         |
| B»WEATHERMAX 4.5               | 0.75           | LAA  | 12 |                            |                            |                            |
| C»LIQUID AMS                   | 2.50           | PMV  | 12 |                            |                            |                            |
| 20A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 84                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| 21A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 88                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| C»N-PAK AMS                    | 2.50           | PMV  | 12 |                            |                            |                            |
| 22A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 88                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| C»ALLIANCE                     | 1.25           | PMV  | 12 |                            |                            |                            |
| 23A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 92                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| C»DESTINY                      | 1.00           | PMV  | 12 |                            |                            |                            |
| D»N-PAK AMS                    | 2.50           | PMV  | 12 |                            |                            |                            |
| 24A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 90                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| C»PREFERENCE                   | 0.25           | PMV  | 12 |                            |                            |                            |
| D»N-PAK AMS                    | 2.50           | PMV  | 12 |                            |                            |                            |
| 25A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 92                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| C»SUPERB HC                    | 0.50           | PMV  | 12 |                            |                            |                            |
| D»N-PAK AMS                    | 2.50           | PMV  | 12 |                            |                            |                            |
| 26A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 95                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| C»SUPERB HC                    | 0.50           | PMV  | 12 |                            |                            |                            |
| D»ALLIANCE                     | 1.25           | PMV  | 12 |                            |                            |                            |
| 27A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 92                         |
| B SELECT (2EC)                 | 0.031          | LAA  | 12 |                            |                            |                            |
| C»AG 03002                     | 1.00           | PMV  | 12 |                            |                            |                            |
| 28A»WEATHERMAX 4.5             | 0.56           | LAA  | 12 | 99                         | 99                         | 83                         |
| B»AG 03002                     | 1.50           | PMV  | 12 |                            |                            |                            |
| LSD (0.05)                     |                |      |    | 1.39                       | 0.915                      | 7.93                       |
| STANDARD DEVIATION             |                |      |    | 0.696                      | 0.457                      | 4.00                       |

» = SUPPLEMENTAL CHEMICAL

## \* TIMING CODES

00 = ----- / UNTREATED TIMING  
09 = ----- / PREEMERGENCE 05/12/2004(1)  
12 = ----- / POST 06/17/2004(2)  
13 = ----- / LPOST 06/23/2004(3)

| H#  | CUSTOM#1 | CUSTOM#2 | EV.DATE    | S# | TYP | SPECIE | STAGE | RAW | PRT | SYM | MTH | CNF | BASIS   | C.M | CTRT | SS | NOTE |
|-----|----------|----------|------------|----|-----|--------|-------|-----|-----|-----|-----|-----|---------|-----|------|----|------|
| 001 | GLXMA    | CON %    | 06/16/2004 | 01 | P   | GLXMA  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 002 | SETFA    | CON %    | 06/16/2004 | 02 | P   | SETFA  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 003 | ZEAMX    | CON %    | 06/16/2004 | 03 | P   | ZEAMX  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 004 | CHEAL    | CON %    | 06/16/2004 | 04 | P   | CHEAL  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 005 | POLPY    | CON %    | 06/16/2004 | 05 | P   | POLPY  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 006 | ABUTH    | CON %    | 06/16/2004 | 06 | P   | ABUTH  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 007 | PHBPU    | CON %    | 06/16/2004 | 07 | P   | PHBPU  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 008 | GLXMA    | CON %    | 06/30/2004 | 01 | P   | GLXMA  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 009 | SETFA    | CON %    | 06/30/2004 | 02 | P   | SETFA  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 010 | ZEAMX    | CON %    | 06/30/2004 | 03 | P   | ZEAMX  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 011 | CHEAL    | CON %    | 06/30/2004 | 04 | P   | CHEAL  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 012 | POLPY    | CON %    | 06/30/2004 | 05 | P   | POLPY  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 013 | ABUTH    | CON %    | 06/30/2004 | 06 | P   | ABUTH  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 014 | PHBPU    | CON %    | 06/30/2004 | 07 | P   | PHBPU  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 015 | GLXMA    | CON %    | 07/16/2004 | 01 | P   | GLXMA  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 016 | SETFA    | CON %    | 07/16/2004 | 02 | P   | SETFA  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |

TITLE: VOLUNTEER RRCORN CONTROL IN RREADY SOYBEAN AS-200

| H#  | CUSTOM#1 | CUSTOM#2 | EV.DATE    | S# | TYP | SPECIE | STAGE | RAW | PRT | SYM | MTH | CNF | BASIS   | C.M | CTR  | SS | NOTE |
|-----|----------|----------|------------|----|-----|--------|-------|-----|-----|-----|-----|-----|---------|-----|------|----|------|
| 017 | ZEAMX    | CON %    | 07/16/2004 | 03 | P   | ZEAMX  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 018 | CHEAL    | CON %    | 07/16/2004 | 04 | P   | CHEAL  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 019 | POLPY    | CON %    | 07/16/2004 | 05 | P   | POLPY  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 020 | ABUTH    | CON %    | 07/16/2004 | 06 | P   | ABUTH  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |
| 021 | PHBPU    | CON %    | 07/16/2004 | 07 | P   | PHBPU  |       | RAW | ALL | CON | %   | --- | 1.00 PL | NO  | 0001 | 0  | N    |

\* SPECIES COMMON NAME - CULTIVAR (IF APPLICABLE)

01 = PIONEER 93B67